





IB 15/80 Ice Blaster

# Innovative cleaning with dry ice: No residue, no chemicals.



# A trendsetting method of cleaning

With its innovative IB 15/80 Ice Blaster Kärcher sets new standards of quality and quantity in surface cleaning.



### Manufacture of dry ice

Dry ice is made by liquefying CO<sub>2</sub> (carbon dioxide) under pressure and then allowing it to expand rapidly. In this process part of the CO<sub>2</sub> evaporates and thus cools the remainder to such an extent that it freezes and creates CO<sub>2</sub> snow at a temperature of -79°C. Dry ice pellets with a diameter of 3 mm are obtained by pressing the CO<sub>2</sub> snow through an appropriate die. Such pellets are available almost everywhere in industrialized countries.



Machine is filled with 3 mm dry ice pellets.



#### Dry ice blast cleaning process

In principle, the dry ice blasting process is very similar to that of sand blasting. Dry ice pellets are used as the blasting medium which sublimates immediately upon impact with the surface being cleaned and returns to the atmosphere as CO<sub>2</sub> gas. There is, therefore, no residue. In the Kärcher Ice Blaster the pellets are injected into a jet of compressed air, accelerated to more than 150 m/s and fired at the surface via the blasting hose with gun and nozzle. Dry ice blasting is ideal for effortlessly removing adhesives, waxes, binding and parting agents, silicone and rubber residue, paints and lacquers, ink and graffiti, oils and greases, tar, bitumen, resins, chewing gum and many other deposits on a wide variety of surfaces without leaving any residue.



Dry ice pellets impact the contaminated surface, causing the dirt to go brittle, then penetrate the cracks thus created in the dirt. Sublimation of the pellets (the change from a solid to a gaseous state) blasts away the dirt without leaving any residue.



# Optimal cleaning results

# Effective 3-phase cleaning principle

The highly effective and intensive cleaning action achieved in dry ice blasting is basically the result of three processes:

# 1) Cleaning with kinetic energy

Dry ice pellets impact the surface being cleaned at a speed of more than 150 m/s.



The abrupt cooling of the contaminated surface by the dry ice pellets (-79°C) causes a thermal shock and produces fine cracks in the contaminant.



# Cleaning by sublimation

3

The dry ice pellets penetrate the cracks created in the contaminant and explode on impact (sublimate), i.e. increase in volume to more than 400 times the original mass. The contaminant is literally blown apart and off the surface.



#### Your benefits

- No dampness, no waste water
- Dry ice sublimates and returns to the atmosphere as CO<sub>2</sub> gas
  No corrosion
- No waste water disposal neces-
- sary

No disassembly necessary

- Machines do not have to be disassembled for cleaning
- Short machine downtimes
- Very economical

- No wear, no erosion
- Dry ice pellets are practically non-abrasive
- Surfaces of equipment being cleaned are not damaged

#### No detergents

- Environment friendly cleaning without additional chemicals or blast abrasives
- No waste water









# Comprehensive range of applications

As cleaning with dry ice is performed completely without detergents and chemical additives and leaves no waste water, it is particularly environment friendly and can even be used in areas where cleaning with water or sand is prohibited by law.



### Automobile industry, foundries



Ideal for:

- Maintenance work in the automobile industry, e.g. for cleaning whole assembly lines,
- machines, engines or transmissions • Drop forging, foundries, welding robots,
- e.g. for cleaning core boxes, injection moulds, tools
- For contamination caused by:
- · Binding and mould parting agents
- Residue of silicone, rubber, polyurethane, thermoplastics, etc.
- Welding splashes, paints and lacquers, greases, oils, etc.





## Printing works



- Ideal for:
- Printing presses and their peripheral equipment, printing cylinders, pits, tools, etc.
- For contamination caused by:
- Dried printing ink
- Oils, greases, etc.







## Steel engineering, metalworking, mech. engineering



#### Ideal for:

Basic and maintenance cleaning of production machines

- Welding robots, conveyors, spraying booths
- For contamination caused by:
- · Oils, greases, paints

## Food, pharmaceutical, cosmetics industry

#### Ideal for:

- Bottling and mixing plants
- Production lines and mechanical handling systems
- Tank and oven cleaning
- For contamination caused by:
- Carbon deposits
- Baked-on stains and encrustations, greases, starch, etc.





### Paper industry

Ideal for:

- Production plant and equipment, cylinders, tanks
- For contamination caused by:
- Deposits of glue and scale, encrusted dust stains, chemical pulp





## Wood and electrical industry

Ideal for:

- Woodworking machines
- Generators, fans, switchgear cabinets, etc.
- For contamination caused by:
- Fire damage, basic cleaning, glue residue, resin





### Plastics and packaging industry

#### Ideal for:

- Injection moulds and production lines
- For contamination caused by:
- Silicone, rubber, polyurethane, thermoplastics, etc.
- Paints and lacquers, greases and oils, etc.





## Local governments



#### Ideal for:

- Escalators, façades
- For contamination caused by:
- Graffiti, chewing gum residue, etc.





ART

# Compact and user-friendly

The new Kärcher IB 15/80 Ice Blaster is not only convincing in terms of its versatility, but also because of its user friendliness.







unintentional operation

7

of ice build-up



# IB 15/80 Ice Blaster Overview:

Technical data		IB 15/80
Order No.		1.574-100.0
Power supply	Ph/V/Hz	1/220-240/50
Connected load	kW	0.6
Dimensions	B x T x H in mm	720 x 850 x 1100
Weight (dry)	kg	90
Sound pressure	dB(A)	max 125
Housing/frame		stainless steel (1.4301)
Compressed air		
Hose coupling		Claw coupling (DIN 3238)
Operating pressure	bar/MPa	3-16/0.3-1.6
Flow rate	m <sup>3</sup> /min	3-11
Air quality		min. Class 3, ISO 8573-1
Dry ice blasting		
Blasting pressure	bar/MPa	3-16/0.3-1.6
Dry ice pellet	ø in mm	3
Dry ice consumption	kg/h	30-100
Dry ice tank capacity	kg	35
Standard accessories	Order No.	Description / function
Blasting gun	4.775-545.0	Ergonomically shaped housing, easy nozzle
		changeover, selector for compressed air and ice or air only
Blasting hose	4.013-037.0	7 m, with quick-action coupling and electric connection
Pencil jet nozzle, small	4.130-418.0	For extreme contamination as well
		as low compressor power
Fan jet nozzle	4.130-423.0	High area coverage with good cleaning power
Fan jet nozzle insert, 10 mm	4.130-422.0	Changes flow rate
Nozzle grease	6.288-072.0	Silicone grease for aluminium threads of nozzles
Nozzle case	6.421-311.0	With foam liner
Mounting kits		
Fan jet nozzle insert, 6 mm	4.130-421.0	Reduces flow rate
Fan jet nozzle insert, 8 mm	4.130-420.0	Reduces flow rate
Scrambler	4.130-416.0	Reduces size of dry ice pellets to fine particles, especially for
		cleaning highly sensitive surfaces
Nozzle extension	4.130-417.0	Makes operation easier in special applications
Handle	6.321-206.0	For use with nozzle extension
Dry ice shovel	4.321-198.0	Stainless steel with insulated handle
Earmuffs	6.321-207.0	Full cups enclose ears
Goggles	6.321-208.0	With side protection and elastic headband
Protective gloves	6.321-210.0	One size fits all



# Ice Blaster - Dry Ice Cleaning Specialist

901 Honeypot Lane Stanmore Middles ex HA7 1AR Tel: 0845 890 3600 Email: sales@chemtec.co.uk Web: www.icecleaners.co.uk